



HOW TO ORDER

BASIC MODEL

CODE

Example
P-06

NOMINAL SIZE

D F G H

63 mm 100 mm 125 mm 150 mm

X

TYPE OF MOUNTING

- 1 WALL / SURFACE / PROJECTION MOUNTING WITH BOTTOM ENTRY
- 2 DIRECT BOTTOM ENTRY
- 4 DIRECT CENTER BACK ENTRY
- 12 CENTER BACK ENTRY WITH FRONT FLANGE
- 13 CENTER BACK ENTRY WITH MOUNTING BRACKET

X

GAUGE CONNECTION (*PREFERRED FOR NS 63 mm.)

- 2BM** 1/4" BSP (M)* **3BM** 3/8" BSP (M) **4BM** 1/2" BSP (M) **4MM** M20 x 1.5 (M)
- 2NM** 1/4" NPT (M)* **3NM** 3/8" NPT (M) **4NM** 1/2" NPT (M)

XXX

Note : Connections like Metric/ PT/ PF/ Flaired/ UNF/ G/ R etc can be provided on request.

RANGE

REFER RANGE TABLE

**0-600
mbar**

OPTIONAL EXTRAS

- PS** AISI 316 CASE & BEZEL
- PW** FIVE POINT CALIBRATION CERTIFICATE
- PU** CALIBRATION CERTIFICATE TRACEABLE TO NATIONAL/ INTERNATIONAL STANDARDS
- QB** INTEGRAL DAMPENING SCREW (AISI 316 SS)
- RH** CUSTOM DESIGNED DIAL
- SU** BRASS MOVEMENT
- RW** PLEXI GLASS
- RX** SHATTERPROOF / SAFETY GLASS
- RZ** TOUGHENED GLASS
- SW** DIAL TAG MARKING
- GH** MATERIAL TEST CERTIFICATES*
- SX** SS TAG PLATE

XX

* MATERIAL TEST CERTIFICATES WILL BE PROVIDED FOR WETTED PARTS ONLY WITH CHEMICAL COMPOSITION TESTING. FOR OTHERS, PLEASE CONSULT FACTORY.

Ordering Example: P-06 - X - X - XXX - 0/600 mbar - XX

FOR OTHER OPTIONAL ITEMS, PLEASE CONTACT FACTORY FOR DELIVERY AND MINIMUM QUANTITY OF ORDER.